



**SureLock
010-600R**

US Patent 7,165,295

- Will not open if the set is more than 50 lbs. (22.6 kg) out of balance, reducing the risk of rigging “runaways”.
- Indicates if the set is balanced, batten heavy, or arbor heavy.
- One piece ASTM A536 ductile iron body.
- 10" (254 mm) handle, powder-coated ductile iron, contoured for comfort and ease of use.
- Two iron cams grip rope with socket head adjustment screw for 5/8" – 1" (15.875–25.4 mm) rope. Adjustment screw has a nylon tip for quiet operation.
- Integral ears for optional padlock.
- Vinyl coated steel oval locking ring.
- May be used on 6" (152 mm) centers or more.
- For use in new projects or as an upgrade to existing rigging systems.
- Rubber bumper to quiet handle when it is opened.

Please Note:

Rope locks are not designed to hold an imbalance of more than 50 lbs. (22.6 kg), nor to be used as a speed control.

Ordering Information

Product Code	Description	RWL	Wt.
010-600R	SureLock	50 lbs. 22.6 kg	20 lbs. 3.6 kg
010-PLOCK	Padlock for Rope Lock	–	1 lb. 0.45 kg
010-533C	Replacement Oval Ring, Vinyl Coated	–	0.1 lb. 0.04 kg

RWL: RWL is maximum load that can be applied to the rope lock which is in "like new" condition and has been properly installed, maintained, and operated.

Dimensions

