



A-Guide System 012-1751

US Patent 6,537,155

- Heavy duty aluminum guide system for counterweight arbors.
- 2" x 3 1/2" x 3/16" (50.8 mm x 88.9 mm x 4.76 mm) guide.
- Significantly less time to install than steel T-Bar.
- 6" (152 mm) and 8" (203 mm) centers are standard, other centers are available.
- A-Guide systems supplied complete with required A-Guide, wall battens, stop battens, splices, adjustable wall knees, bolts, nuts, and washers.
- Adjustable wall knees allow simple, on site adjustment to meet field conditions.
- Vertical A's are connected to wall battens with self-aligning clamps, for fast installation. Pre-punched horizontal wall battens and stop battens are pre-punched 1 3/4" x 1 3/4" x 3/16" (44.5 mm x 44.5 mm x 4.76 mm) steel angle, with holes on 2" (50.8 mm) centers. These allow simple adjustment of guide location to accommodate field conditions.
- Optional 2" x 2" (50.8 mm x 50.8 mm) hardwood or hardwood with neoprene bumpers are available for stop battens.

Ordering Information

Guide systems are ordered in linear feet of guide required (number of runs of A x height of guide).

Product Code	Description	Wt.
012-1751	A-Guide System, black anodized finish	4 lbs./ft. 5.9 kg/m
012-1H	2" x 2" (50.8 mm x 50.8 mm) Hardwood stop batten	3 lbs./ft. 4.46 kg/m
012-1N	2" x 2" (50.8 mm x 50.8 mm) Hardwood stop batten w/1/4" (6.35 mm) Neoprene	4 lbs./ft. 5.9 kg/m