



Galvanized Utility Cable
020-125

- 7 x 19 Galvanized Utility Cable is used for lift lines, guide wires, and other applications requiring an economical wire rope with good strength and flexibility.
- Manufactured to Federal Specification RRW-410E.
- Test certificates are available at extra cost.
- Sold in 2500' (762 m) rolls.
- Other types of wire rope are available for special applications.

Ordering Information

Product Code	Description	RWL	Wt.
2,500' (762 m) Rolls, wt. per foot (meter)			
020-125	1/8" (3.175 mm) Galvanized Utility Cable	250 lbs. 113 kg	0.03 lb. 0.01 kg
020-187	3/16" (4.76 mm) Galvanized Utility Cable	537 lbs. 243 kg	0.07 lb. 0.03 kg
020-250	1/4" (6.35 mm) Galvanized Utility Cable	875 lbs. 397 kg	0.11 lb. 0.05 kg
020-312	5/16" (7.9 mm) Galvanized Utility Cable	1225 lbs. 556 kg	0.18 lb. 0.08 kg
020-375	3/8" (9.5 mm) Galvanized Utility Cable	1800 lbs. 816 kg	0.25 lb. 0.11 kg
500' (152.4 m) Convenience Rolls, wt. per roll			
020-125-5	1/8" (3.175 mm) Galvanized Utility Cable	250 lbs. 113 kg	15 lbs. 6.8 kg
020-375-5	3/8" (9.5 mm) Galvanized Utility Cable	1800 lbs. 816 kg	90 lbs. 40.8 kg

RWL is based on an 8:1 safety factor.