



**Pin Rail with Belaying Pins
and Sand Bag**
015-520R

- Pin rails are designed to allow the user to insert belaying pins to tie-off rope rigging.
- The pin rail is made of 3 1/2" (88.9 mm) pipe with holes for belaying pins on 12" (305 mm) centers supported by 4" (102 mm) channel legs.
- Double pin rails have two pipes so that non-moving pieces may be tied off to one pipe and the other used for the active sets. Also for double trims.
- Wood and steel belaying pins are available.
- Sand bags may be used to counterbalance the load. Sand bags are made from ballistic nylon, with a forged safety hook, and Velcro™ closure. Dry sand (not supplied) can be added or removed to accurately balance a load.

Ordering Information

Product Code	Description	Wt.
Pin Rails		
015-520R	Single Pin Rail	25 lbs./ft. 37 kg/m
015-520D	Double Pin Rail	45 lbs./ft. 66.9 kg/m
Belaying Pins		
015-249	21" (533 mm) Wooden Belaying Pin, 1 5/32" (29.37 mm) Diameter	1 lb./ea. 0.45 kg/ea.
015-439	Steel Belaying Pin, 3/4" (19 mm) Diameter	2 lbs./ea. 0.9 kg/ea.
015-449	Steel Belaying Pin, 1 1/16" (29.3 mm) Diameter	2.2 lbs./ea. 1 kg/ea.
Sand Bags		
015-2596	25 lb. (11.3 kg) Sand Bag	1 lb./ea. 0.45 kg/ea.
015-5096	50 lb. (22.6 kg) Sand Bag	1 lb./ea. 0.45 kg/ea.
015-10096	100 lb. (45.3 kg) Sand Bag	2 lbs./ea. 0.9 kg/ea.
015-15096	150 lb. (68 kg) Sand Bag	2 lbs./ea. 0.9 kg/ea.

Dimensions

