



T-Bar Guide System
012-1500

- Used to guide counterweight arbors.
- 6" (152 mm) and 8" (203 mm) centers are standard, other centers are available.
- T-Bar systems supplied complete with required T-Bar, steel wall batten angles, stop battens, splice bars, U-clips, adjustable wall knees, bolts, nuts, and washers.
- Adjustable wall knees allow simple, on site adjustment to meet field conditions.
- Vertical T's are pre-punched 1 1/2" x 1 1/2" x 3/16" (38.1 mm x 38.1 mm x 4.76 mm) steel members.
- Horizontal wall battens & stop battens are pre-punched 1 3/4" x 1 3/4" x 3/16" (44.5 mm x 44.5 mm x 4.76 mm) steel angle.
- Optional 2" x 2" (50.8 mm x 50.8 mm) hardwood or hardwood with neoprene bumpers are available for stop battens.

Ordering Information

Guide systems are ordered in linear feet of guide required (number of runs of T x height of guide).

Product Code	Description	Wt.
012-1500	T-Bar Guide System (> 700 feet [$> 215\text{ m}$])	4 lbs./ft. 5.9 kg/m
012-1501	T-Bar Guide System (< 700 feet [$> 215\text{ m}$])	4 lbs./ft. 5.9 kg/m
012-1H	2" x 2" (50.8 mm x 50.8 mm) Hardwood stop batten	3 lbs./ft. 4.46 kg/m
012-1N	2" x 2" (50.8 mm x 50.8 mm) Hardwood stop batten w/ 1/4" (6.35 mm) Neoprene	4 lbs./ft. 5.9 kg/m

Dimensions

