



### A-Guide System 012-1751

US Patent 6,537,155

- Heavy duty aluminum guide system for counterweight arbors.
- 2" x 3 1/2" x 3/16" guide.
- Significantly less time to install than steel T-Bar.
- 6" and 8" centers are standard, other centers are available.
- A-Guide systems supplied complete with required A-Guide, wall battens, stop battens, splices, adjustable wall knees, bolts, nuts and washers.
- Adjustable wall knees allow simple, on site adjustment to meet field conditions.
- Vertical A's are connected to wall battens with self aligning clamps, for fast installation pre-punched horizontal wall battens and stop battens pre-punched 1 3/4" x 1 3/4" x 3/16" steel angle, with holes on 2" centers. These allow simple adjustment of guide location to accommodate field conditions.
- Optional 2" x 2" hardwood or hardwood with neoprene bumpers are available for stop battens.

### Ordering Information

Guide systems are ordered in linear feet of guide required (number of runs of A x height of guide).

Product Code	Description	Wt.
012-1751	A-Guide System, black anodized finish	4 lbs. / ft.
012-1H	2" x 2" Hardwood stop batten	3 lbs. / ft.
012-1N	2" x 2" Hardwood stop batten w/1/4" Neoprene	4 lbs. / ft.