



J-Guide/T-Bar Arbor, SP
007-15X04

- Used in J-Guide / T-Bar guided systems to hold counterweight that balances the batten load.
- Arbor tops and bottoms are fabricated 1/4" steel weldments with a bolt and spacer for hand line termination.
- Arbor tops are punched to accept 8 cables.
- Two 3/4" steel arbor rods have three nuts at top and bottom.
- Each rod has a retaining collar with a thumbscrew incorporating an easy to grip plastic knob.
- Front collar is welded to top spreader plate for additional security.
- 12 gauge steel spreader plate every two feet (minimum 2). Labels on the back bar show safety information and proper location for spreader plates.
- 3/8" x 3" steel back bar, with two guide assemblies.
- Standard polypropylene guide shoes allow for on site adjustment for 6" or 8" set centers; other shoe types and centers are available.
- Arbors are provided with easy to read, self adhesive set numbers.

Ordering Information

Product Code	Length*	Capacity* 4" Weights	Capacity* 6" Weights	Wt.
007-15X04	4'	504	782	56 lbs.
007-15X05	5'	672	1043	63 lbs.
007-15X06	6'	841	1303	71 lbs.
007-15X07	7'	1009	1564	78 lbs.
007-15X08	8'	1177	1825	85 lbs.
007-15X09	9'	1345	2086	92 lbs.
007-15X10	10'	1514	2346	99 lbs.
007-15X11	11'	1682	2607	106 lbs.
007-15X12	12'	1850	2868	113 lbs.
007-15X13	13'	2018	3129	122 lbs.



Eye Nut
048-3/4EN

*OVERALL LENGTH IS 8" LONGER THAN THE NOMINAL LENGTH.

+AVERAGE CAPACITY USING J.R. CLANCY STEEL COUNTERWEIGHTS.

RWL: RWL is maximum load that can be applied to the arbor which is in "like new" condition and has been properly installed, maintained and operated.

Options:

Product Code	Description	Wt.
048-3/4EN	3/4" Eye Nut	2 lbs.

Dimensions

