



**Pin Rail with Belaying Pins  
and Sand Bag**  
015-520R

- Pin rails are designed to allow the user to insert belaying pins to tie-off rope rigging.
- The pin rail is made of 3 1/2" pipe with holes for belaying pins on 12" centers supported by 4" channel legs.
- Double pin rails have two pipes so that non-moving pieces may be tied off to one pipe and the other used for the active sets. Also for double trims.
- Wood and steel belaying pins are available.
- Sand bags may be used to counterbalance the load. Sand bags are made from ballistic nylon, with a forged safety hook, and Velcro™ closure. Dry sand (not supplied) can be added or removed to accurately balance a load.

### Ordering Information

Product Code	Description	Wt.
<b>Pin Rails</b>		
015-520R	Single Pin Rail	25 lbs. / ft.
015-520D	Double Pin Rail	45 lbs. / ft.
<b>Belaying Pins</b>		
015-249	21" Wooden Belaying Pin, 1 5/32" Diameter	1 lb. / ea.
015-439	Steel Belaying Pin, 3/4" Diameter	2 lbs. / ea.
015-449	Steel Belaying Pin, 1 1/16" Diameter	2.2 lbs. / ea.
<b>Sand Bags</b>		
015-2596	25 lb. Sand bag	1 lb. / ea.
015-5096	50 lb. Sand bag	1 lb. / ea.
015-10096	100 lb. Sand bag	2 lbs. / ea.
015-15096	150 lb. Sand bag	2 lbs. / ea.

### Dimensions

