



**PowerLift Automated Hoist
018-P0220VE**



**PowerLift Automated Hoist
018-P0220T**

US Patent 7,562,863



Intertek

3167743

Conforms to UL STD 1340

PowerLift® E-Series Hoists

Movement on stage is part of the excitement of live performance. The five variable speed models offer combinations of speeds and lifting speeds selection to provide the action you need. Variable speed hoists let you make subtle changes, or fast dramatic moves — and anything in between. If your theatre is used for dramas or musicals, you'll want the Performance Line. Variable speed up to 180 fpm and capacities up to 2,000 lbs.

Model	Speed	Capacity	HP	Travel	Weight
018-P0220VE	0 - 20 fpm	2,000 lbs	1.5	65'	750 lbs. ea.
018-P1212VE	0 - 120 fpm	1,200 lbs	5.0	65'	770 lbs. ea.
018-P1220VE	0 - 120 fpm	2,000 lbs	7.5	65'	800 lbs. ea.
018-P1812VE	0 - 180 fpm	1,200 lbs	7.5	65'	800 lbs. ea.
018-P1817VE	0 - 180 fpm	1,750 lbs	10	65'	800 lbs. ea

These units are used with the SceneControl® or Altus™ consoles, allowing accurate positioning. All units have up to 7 lift lines. Hoists require 3 phase power at 208, 230, or 460 VAC. Please confirm voltage at time of ordering (380 and 575 VAC and 50 Hz hoists are available for international projects).

Options:

- 018-PLLOAD Load monitoring option
- 014-933 Cover

PowerLift® T-Series Hoist

When you need accurate, repeatable positioning, this ingenious fixed speed hoist is the economical solution. The SureTarget™ controller lets you set four preset stops — ideal for your lighting and other utility sets. T-series hoists can be used with a cable management for your front of house lighting, house lighting, or onstage lighting sets. SureTarget moves sets to their preset position exactly, without the need for guesswork or bumping and jogging a set in to the right spot.

Model	Speed	Capacity	HP	Travel	Weight
018-P0220T	20 fpm	2,000 lbs	1.5	65'	750 lbs. ea.

This unit is provided with the SureTarget controller. All units have up to 7 lift lines. Hoists require 3 phase power at 208, 230, or 460 VAC. Please confirm voltage at time of ordering (380 and 575 VAC and 50 Hz hoists are available for international projects).

Options:

- 014-933 Cover
- Cable handling systems, including pantographs, cable reels, or cable cradles.

Application drawings and more information available for download on our site.



Design, Manufacture and Installation of Theatrical Equipment Worldwide

7041 Interstate Island Road ▪ Syracuse, New York USA 13209-9713

315-451-3440 ▪ 1-800-836-1885 ▪ Fax: 315-451-1766 ▪ www.jrclancy.com

© J.R. Clancy 2009

