



**T-Bar Guide System  
012-1500**

- Used to guide counterweight arbors.
- 6" and 8" centers are standard, other centers are available.
- T-Bar systems supplied complete with required T-Bar, steel wall batten angles, stop battens, splice bars, U-clips, adjustable wall knees, bolts, nuts and washers.
- Adjustable wall knees allow simple, on site adjustment to meet field conditions.
- Vertical T's are pre-punched  $1\frac{1}{2}" \times 1\frac{1}{2}" \times \frac{3}{16}"$  steel members.
- Horizontal wall battens & stop battens are pre-punched  $1\frac{3}{4}" \times 1\frac{3}{4}" \times \frac{3}{16}"$  steel angle.
- Optional 2" x 2" hardwood or hardwood with neoprene bumpers are available for stop battens.

### Ordering Information

Guide systems are ordered in linear feet of guide required (number of runs of T x height of guide).

Product Code	Description	Wt.
012-1500	T-Bar Guide System (> 700 feet)	4 lbs. / ft.
012-1501	T-Bar Guide System (< 700 feet)	4 lbs. / ft.
012-1H	2" x 2" Hardwood stop batten	3 lbs. / ft.
012-1N	2" x 2" Hardwood stop batten w/ $\frac{1}{4}"$ Neoprene	4 lbs. / ft.

### Dimensions

